E-SHINE DISPLAY CO., LTD. EX1602A

Dimension Drawing



Feature:

1. 2-line x16 characters display; 5x8 dots with cursor
2. Built-in controller NT7605
3. +5V power supply(also available for +3.3V)
4. 1/16 Duty cycle
5. STN or FSTN Mode
6. Match all kind colors of LED back light
7. ROHS compliant

Interface Pin Connections

PIN NO.	Symbol	Function
1	VSS	GND
2	VDD	+5V or +3.3V
3	V0	Contrast adjustment
4	RS	H/L Register select signal
5	R/W	H/L Read/Write signal
6	E	H/L Enable signal
7	DB0	H/L Data bus line
8	DB1	H/L Data bus line
9	DB2	H/L Data bus line
10	DB3	H/L Data bus line
11	DB4	H/L Data bus line
12	DB5	H/L Data bus line
13	DB6	H/L Data bus line
14	DB7	H/L Data bus line

Mechanical Data

Item	Standard	Unit
Module dimension	104.4 x 50.6	mm
Viewing area	91.4 x 28.6	mm
Character size	18.72 x 8.84	mm
Dots size	1.64 x 2.2	mm

Absolute Maximum Rating

Item	Symbol	Standard			Unit
		Min	Typ	Max	
Power supply	VDD-VSS	-0.3	---	7.0	V
Input voltage	VI	-0.3	---	VDD+0.3	

Electronical Characteristics

Item	Symbol	Condition	Standard			Unit
			Min	Typ	Max	
Input voltage	VDD	+5.0V	4.5	5.0	5.5	V
		+3.3V	2.7	3.3	4.5	V
Supply current	I_{DD}	VDD=5V	----	125	160	uA
Recommended LCD driving voltage for normal temp version module	VDD-V0 (VDD=5V)	-20°C	4.9	5.2	5.5	V
		0°C	4.5	4.8	5.1	
		25°C	4.1	4.5	4.8	
		50°C	3.8	5.0	4.4	
		70°C	3.5	4.2	5.5	
LED forward voltage	VF	25°C	----	3.1	3.3	V
LED forward current	IF	25°C Edge	----	15	20	mA

Display Character Address Code:

Display position	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
DDRAM address	00	01	02	--	--	--	--	--	--	--	--	--	--	--	0EH	0FH
DDRAM address	40	41	42	--	--	--	--	--	--	--	--	--	--	--	4EH	4FH

www.e-shinedisplay.com